

AS568B	O型圈的尺寸（单位：mm）				AS568B	O型圈的尺寸（单位：mm）				AS568B	O型圈的尺寸（单位：mm）				AS568B	O型圈的尺寸（单位：mm）			
公称编号	线径	C/S	内径	d	公称编号	线径	C/S	内径	d	公称编号	线径	C/S	内径	d	公称编号	线径	C/S	内径	d
001	1.02	±0.07	0.74	±0.10	034	1.78	±0.07	53.7	±0.25	117	2.62	±0.07	20.29	±0.15	150	2.62	±0.07	72.69	±0.38
002	1.27		1.07		035			56.87		118			21.89		151			75.87	
003	1.52		1.42		036			60.05		119			23.47		152			82.22	
004	1.78		1.78	±0.12	037			63.22	±0.38	120			25.07		153			88.57	±0.58
005			2.57		038			66.4		121			26.64		154			94.92	
006			2.9		039			69.57		122			28.24		155			101.27	
007			3.68		040			72.75		123			29.82		156			107.62	
008			4.47		041			75.92		124			31.42		157			113.97	
009			5.28		042			82.27		125			32.99		158			120.32	
010			6.07		043			88.62		126			34.59		159			126.67	
011			7.65		044			94.97		127			36.17		160			133.02	
012			9.25		045			101.32		128			37.77		161			139.37	
013			10.82		046			107.67		129			39.34		162			145.72	
014			12.42	047	114.02			130	40.94	163			152.07						
015			14	048	120.37			131	42.52	164			158.42						
016			15.6	049	126.72			132	44.12	165			164.77						
017			17.17	050	133.07			133	45.69	166			171.12						
018			18.77					134	47.29	167			177.47						
019			20.35	102	2.62	±0.07	1.24	±0.12	135	48.9			168	183.82					
020			21.95	103			2.06		136	50.47			169	190.17					
021			23.52	104			2.84		137	52.07			170	196.52					
022			25.12	105			3.63		138	53.64			171	202.87					
023			26.7	106			4.42		139	55.24			172	209.22					
024			28.3	107			5.23		140	56.82			173	215.57					
025			29.87	108			6.02		141	58.42			174	221.92					
026			31.47	109			7.59		142	59.99			175	228.27					
027			33.05	110			9.19		143	61.6			176	234.62					
028			34.65	111			10.77		144	63.17			177	240.97					
029			37.82	112			12.37		145	64.77			178	247.32					
030			41	113			13.94		146	66.34			169	190.17					
031			44.17	114			15.54		147	67.94			170	196.52					
032			47.35	115			17.12		148	69.52			171	202.87					
033			50.52	116			18.72		149	71.12			172	209.22					

AS568B	O型圈的尺寸 (单位 : mm)				AS568B	O型圈的尺寸 (单位 : mm)				AS568B	O型圈的尺寸 (单位 : mm)				AS568B	O型圈的尺寸 (单位 : mm)			
公称编号	线径	C/S	内径	d	公称编号	线径	C/S	内径	d	公称编号	线径	C/S	内径	d	公称编号	线径	C/S	内径	d
201	3.53	±0.10	4.34	±0.12	234	3.53	±0.10	75.79	±0.38	267	3.53	±0.10	209.14	±0.76	324	5.33	±0.12	34.29	±0.15
202			5.94		235			78.97		268			215.49		325			37.46	±0.25
203			7.52		236			82.14		269			221.84		326			40.64	
204			9.12		237			85.32		270			228.19		327			43.82	
205			10.69		238			88.49		271			234.54		328			46.99	
206			12.29		239			91.67		272			240.89		329			50.16	
207			13.87		240			94.84		273			247.24		330			53.34	
208			15.47		241			98.02		274			253.59		331			56.52	
209			17.04		242			101.19		275			266.29		332			59.69	
210			18.64		243			104.37		276			278.99		333	5.33	±0.12	62.86	
211			20.22	±0.15	244			107.54	±0.58	277			291.69	±1.14	334			66.04	±0.38
212			21.82		245			110.72		278			304.39		335			69.22	
213			23.39		246			113.89		279			329.79		336			72.39	
214			24.99		247			117.07		280			355.19		337			75.56	
215			26.57		248			120.24		281			380.59		338			78.74	
216			28.17		249			123.42		282			405.26		339			81.92	
217			29.74		250			126.59		283			430.66		340			85.09	
218			31.34		251			129.77	±0.76	284			456.06		341			88.26	
219			32.92		252			132.94		309	5.33	±0.12	10.46	±0.15	342			91.44	
220			34.52	±0.25	253			136.12		310			12.06		343			94.62	
221			36.09		254			139.29		311			13.64		344			97.79	
222			37.69		255			142.47		312			15.24		345			100.96	
223			40.87		256			145.64		313			16.81		346			104.14	
224			44.04		257			148.82		314			18.42		347			107.32	
225			47.22		258			151.99		315			19.99		348			110.49	
226			50.39		259			158.34		316			21.59		349			113.66	
227			53.57		260			164.69		317			23.16		350			116.84	
228			56.74		261			171.04		318			24.76		351			120.02	
229			59.92	±0.38	262			177.39		319			26.34		352			123.19	
230			63.09		263			183.74		320			27.94		353			126.36	
231			66.27		264			190.09		321			29.51		354			129.54	±0.58
232			69.44		265			196.44		322			31.12		355			132.72	
233			72.62		266			202.79		323			32.69		356			135.89	

AS568B	O型圈的尺寸 (单位 : mm)		
公称编号	线径 C/S	内径 d	
357	5.33	±0.12	139.07
358			142.24
359			145.42
360			148.59
361			151.77
362			158.12
363			164.47
364			170.84
365			177.17
366			183.52
367			189.87
368			196.22
369			202.57
370			208.92
371			215.26
372			221.62
373		±0.76	227.96
374			234.32
375			240.67
376			247.02
377			253.37
378			266.07
379			278.77
380			291.47
381			304.17
382			329.57
383			354.97
384			380.37
385		±1.14	405.26
386			430.66
387			456.06
388			481.46
389			506.86

AS568B	O型圈的尺寸 (单位 : mm)		
公称编号	线径 C/S	内径 d	
390	5.33	±0.12	532.26 ±1.14
391			557.66
392			582.68
393			608.08
394			633.48
395			658.88
425	6.99	±0.15	113.66
426			116.84
427			120.02
428			123.19
429			126.36
430			129.54
431			132.72
432			135.89
433			139.06
434			142.24
435		±0.58	145.42
436			148.59
437			151.76
438			158.12
439			164.46
440			170.82
441			177.16
442		±0.76	183.52
443			189.86
444			196.22
445			202.56
446			215.26
447			227.96
448			240.66
449			253.36
450			266.06
451			278.76

AS568B	O型圈的尺寸 (单位 : mm)		
公称编号	线径 C/S	内径 d	
452	6.99	±0.15	291.46
453			304.16
454			316.86
455			329.56
456			342.26
457			354.96
458			367.66
460			380.36
461			405.26
462			417.96
463			430.66
464		±1.14	443.36
465			456.06
466			468.76
467			481.46
468			494.16
469			506.86
470			532.46
471			557.66
472			582.68
473			608.08
474			633.48
475			658.88
901	1.42	±0.07	4.7
902	1.63		6.07
903	1.83		7.64
904	1.83		8.92
905	1.98		10.52
906	2.08		11.89
907	2.21		13.46
908	2.21		16.36
909	2.46		17.93
910	2.46		19.18

AS568B	O型圈的尺寸 (单位 : mm)		
公称编号	线径 C/S	内径 d	
911	2.95	±0.1	21.92 ±0.12
912			23.47
913			25.04
914			26.59
916			29.74
918	3	±0.25	34.42
920			37.46
924			43.69
928			53.09
932			59.36

(单位 : 毫米/mm)

: 其他尺寸亦可提供 !

订货示例 :

O型圈 美国标准AS568B 标准号008

内径 (ID)4.47mm

线径 (C/S)1.78mm

材料 : Viton75B (氟橡胶75度黑)

订货号 : ORAR00008-V75B

